



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	38,2	
3,00 mm	h 7	122,5	
4,00 mm	h 7	136,9	
5,00 mm	h 7	328,9	
6,00 mm	h 8	172,5	(800,0)
8,00 mm	h 8	311,6	(400,0)
10,00 mm	h 8	419,4	(400,0)
12,00 mm	h 8	352,1	(400,0)
14,00 mm	h 8	389,2	
15,00 mm	h 8	472,1	
16,00 mm	h 9	724,4	
18,00 mm	h 9	583,4	
20,00 mm	h 9	600,8	(300,0)
22,00 mm	h 9	641,8	
25,00 mm	h 9	2558,4	(1500,0)
30,00 mm	h 9	957,5	(1500,0)
35,00 mm	h 9	710,7	(300,0)
40,00 mm	-0/+0.100	1340,4	(2500,0)
45,00 mm	-0/+0.100	921,0	(500,0)
50,00mm	-0/+0.100	767,9	(500,0)
55,00 mm	-0/+0.100	1790,2	
60,00 mm	-0/+0.120	2731,2	
65,00 mm	-0/+0.120	872,1	(800,0)
70,00 mm	-0/+0.140	812,1	
75,00 mm	-0/+0.140	483,2	
80,00 mm	-0/+0.140	1263,0	
85,00 mm	-0/+0.140	474,0	
90,00 mm	-0/+0.200	765,2	
100,00 mm	-0/+0.500	899,0	(400,0)
105,00 mm	-0/+0.500	762,2	
110,00 mm	-0/+0.500	545,3	(300,0)
115,00 mm	-0/+0.500	499,0	
120,00 mm	-0/+0.500	5,0	(1200,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
130,00 mm	-0/+0.500	971,8	(1200,0)
140,00 mm	-0/+0.500	1115,4	(400,0)
150,00 mm	-0/+0.500	628,6	(300,0)
160,00 mm	-0/+0.500	232,6	(1500,0)
170,00 mm	-0/+0.500	605,5	
180,00 mm	-0/+0.500	224,4	(600,0)
190,00 mm	-0/+0.500	347,9	
200,00 mm	-0/+0.500	587,0	
225,00 mm	-0/+0.500	680,9	
230,00 mm	-0/+0.500	1125,0	
250,00 mm	-0/+0.500	1243,8	
280,00 mm	-0/+0.500	478,8	
305,00 mm	-0/+0.500	317,3	(330,0)
330,00 mm	-0/+0.500	1719,4	
350,00 mm	-0/+0.500	508,6	

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	270,8	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	48,2	
3,00 mm	h 7	225,3	(150,0)
4,00 mm	h 7	357,5	(800,0)
5,00 mm	h 7	1941,6	
6,00 mm	h 8	934,3	(1500,0)
8,00 mm	h 8	1770,4	
10,00 mm	h 8	1026,8	(1000,0)
12,00 mm	h 8	971,4	(1210,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
14,00 mm	h 8	443,5	(300,0)
15,00 mm	h 8	258,1	(200,0)
16,00 mm	h 9	2,4	(2300,0)
18,00 mm	h 9	364,0	(300,0)
19,05 mm	h9	0,0	(702,8)
20,00 mm	h 9	2290,8	
22,00 mm	h 9	477,6	(400,0)
25,00 mm	h 9	2080,0	
		0,0	(800,0)
25,40 mm	h9	1094,4	(1189,2)
26,00 mm	h 9	480,4	(3200,0)
30,00 mm	h 9	3136,7	(1200,0)
		0,0	(1000,0)
31,75 mm	h9	1217,0	(1715,6)
35,00 mm	h 9	2092,2	(900,0)
		0,0	(400,0)
36,00 mm	h 9	477,2	
40,00 mm	-0/+0.100	820,7	(800,0)
		0,0	(2500,0)
45,00 mm	-0/+0.100	806,5	(1300,0)
		0,0	(800,0)
50,00 mm	-0/+0.100	1067,5	(500,0)
		0,0	(800,0)
55,00 mm	-0/+0.100	484,5	(600,0)
		0,0	(300,0)
60,00 mm	-0/+0.120	2242,7	
		0,0	(700,0)
65,00 mm	-0/+0.120	1250,0	(300,0)
		0,0	(700,0)
70,00 mm	-0/+0.140	870,1	(300,0)
		0,0	(1200,0)
75,00 mm	-0/+0.140	705,3	(600,0)
		0,0	(300,0)
80,00 mm	-0/+0.140	1098,8	(200,0)
		0,0	(500,0)
80,00 mm	-0/+0.140	151,2	(200,0)
85,00 mm	-0/+0.140	218,0	(1040,0)
90,00 mm	-0/+0.200	949,5	
		0,0	(400,0)
		0,0	(5029,2)

Office and warehouse: TITANIUM GATEWAY AB Allmäningsvägen 59 * SE17678 Järfälla

P: +46 (0)8 580 80 250 • F: +46 (0)8 580 80 259 • W: www.titanium-gateway.com • E: info@titanium-gateway.com

100,00 mm	-0/+0.500	2244,6	
110,00 mm	-0/+0.500	886,3	
		0,0	(400,0)
120,00 mm	-0/+0.500	148,3	
		0,0	(600,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
130,00 mm	-0/+0.500	1182,9	
140,00 mm	-0/+0.500	3120,5	
		0,0	(500,0)
150,00 mm	-0/+0.500	743,3	
160,00 mm	-0/+0.500	599,9	
170,00 mm	-0/+0.500	1307,5	
180,00 mm	-0/+0.500	97,1	
		0,0	(800,0)
190,00 mm	-0/+0.500	369,1	
200,00 mm	-0/+0.500	527,0	
225,00 mm	-0/+0.500	403,2	
230,00 mm	-0/+0.500	309,0	
		0,0	(1000,0)
250,00 mm	-0/+0.500	811,5	
255,00 mm	-0/+0.500	113,8	
280,00 mm	-0/+0.500	938,6	
		0,0	(560,0)
		0,0	(659,6)
330,00 mm	-0/+0.500	578,8	
350,00 mm	-0/+0.500	500,4	
		0,0	(330,0)

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
0,4 x 1000 x 2000 mm	77,6	
0,5 x 1000 x 2500 mm	178,2	(197,4)
0,6 x 1000 x 2500 mm	6,8	(2530,0)
0,7 x 1000 x 2500 mm	309,5	
0,8 x 1000 x 2500 mm	421,2	(1511,5)
1,0 x 1250 x 3000 mm	1062,3	(3672,0)
1,5 x 1250 x 3000 mm	1715,2	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Condition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
2,0 x 1250 x 3000 mm	2573,9	(3004,0)
2,5 x 1250 x 3000 mm	212,6	
3,0 x 1250 x 3000 mm	1097,4	(604,8)
4,0 x 1000 x 2000 mm	919,2	
5,0 x 1000 x 2000 mm	416,7	
6,0 x 1000 x 2000 mm	434,2	

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0 x 1000 x 2000 mm	239,5	
1,0 x 1250 x 2000 mm	293,6	
1,5 x 1000 x 2000 mm	188,5	(203,0)
1,5 x 1250 x 2000 mm	184,4	
1,5 x 1250 x 2500 mm	272,3	
10,0 x 1500 x 2500 mm	1148,7	(338,0)
12,0 x 1500 x 2500 mm	876,5	(215,0)
15,0 x 1500 x 2500 mm	676,8	(530,0)
2,0 x 1000 x 2000 mm	879,7	
20,0 x 1500 x 2500 mm	1018,8	
25,0 x 1500 x 2500 mm	1008,9	
3,0 x 1000 x 2000 mm	889,2	
30,0 x 1500 x 2500 mm	347,1	
35,0 x 1500 x 2000 mm	697,0	
4,0 x 1000 x 2000 mm	469,2	(613,0)
40,0 x 1500 x 2000 mm	269,8	(552,0)
5,0 x 1000 x 2000 mm	398,5	
	0,0	(690,0)
6,0 x 1000 x 2000 mm	116,6	(325,0)
6,0 x 1500 x 2500 mm	365,9	
	0,0	(552,0)
	0,0	(632,0)
8,0 x 1500 x 2500 mm	69,9	(812,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1,0 x 1000 x 2000 mm	68,3	(298,0)
1,5 x 1000 x 2000 mm	161,3	
10,0 x 1000 x 2000 mm	171,7	(360,0)
12,0 x 1000 x 2000 mm	381,8	
15,0 x 1000 x 2000 mm	179,5	(270,0)
2,0 x 1000 x 2000 mm	401,0	
20,0 x 1000 x 2000 mm	189,2	(360,0)
25,0 x 1000 x 2000 mm	201,2	(225,0)
3,0 x 1000 x 2000 mm	13,1	(406,0)
3,0 x 1000 x 2400 mm	269,3	
3,0 x 1250 x 2500 mm	43,2	
30,0 x 1000 x 2000 mm	406,6	
	0,0	(227,7)
4,0 x 1000 x 2000 mm	483,7	
40,0 x 1000 x 2000 mm	808,6	(365,0)
5,0 x 1000 x 2000 mm	513,4	
50,0 x 1000 x 2000 mm	271,9	(450,0)
6,0 x 1000 x 2000 mm	220,0	(325,0)
60,0 x 1000 x 2000 mm	183,0	(1080,0)
70,0 x 1000 x 2000 mm	636,0	
8,0 x 1000 x 2000 mm	295,0	(144,0)

Titanium Grade 7 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, pickled surface

Dimension	QTY (kg)	Incoming
1,0 x 1000 x 2000 mm	0,8	(90,0)
2,0 x 1000 x 2000 mm	57,5	
3,0 x 1000 x 2000 mm	55,5	

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	92,9	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
12,7 x 12,7	161,6	
19,05 x 19,05	208,4	
25,4 x 6,35	141,0	
25,4 x 12,7	39,8	
25,4 x 25,4	385,7	
35,0 x 35,0	0,0	(331,8)

Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	40,0	
1,6 mm	30,0	
2,0 mm	35,0	
2,4 mm	45,0	
3,2 mm	45,0	

Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	0,0	(40,0)
2,4 mm	10,0	(20,0)