



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	48,4	
3,00 mm	h 7	74,9	
4,00 mm	h 7	157,2	
5,00 mm	h 7	188,4	
6,00 mm	h 8	714,2	
8,00 mm	h 8	336,3	
10,00 mm	h 8	366,3	(300,0)
12,00 mm	h 8	475,5	
14,00 mm	h 8	382,8	
15,00 mm	h 8	457,3	
16,00 mm	h 9	1594,2	
18,00 mm	h 9	533,2	
20,00 mm	h 9	173,2	(300,0)
22,00 mm	h 9	2,5	(1200,0)
25,00 mm	h 9	643,8	(2186,6)
30,00 mm	h 9	1429,3	
35,00 mm	h 9	991,2	(1000,0)
40,00 mm	-0/+0.100	1913,6	(1114,0)
45,00 mm	-0/+0.100	389,0	(400,0)
50,00mm	-0/+0.100	791,9	
55,00 mm	-0/+0.100	2259,2	
60,00 mm	-0/+0.120	2435,0	
65,00 mm	-0/+0.120	677,7	
70,00 mm	-0/+0.140	367,4	
80,00 mm	-0/+0.140	397,3	
90,00 mm	-0/+0.200	399,7	
100,00 mm	-0/+0.500	519,1	
110,00 mm	-0/+0.500	110,3	(260,0)
120,00 mm	-0/+0.500	385,5	
130,00 mm	-0/+0.500	823,6	
140,00 mm	-0/+0.500	1206,9	
150,00 mm	-0/+0.500	329,3	
160,00 mm	-0/+0.500	301,9	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
170,00 mm	-0/+0.500	365,0	
180,00 mm	-0/+0.500	91,0	(345,0)
190,00 mm	-0/+0.500	348,5	
200,00 mm	-0/+0.500	302,6	
225,00 mm	-0/+0.500	283,3	
250,00 mm	-0/+0.500	385,7	
280,00 mm	-0/+0.500	503,0	
305,00 mm	-0/+0.500	315,5	
305,00 mm	-0/+0.500	337,4	
350,00 mm	-0/+0.500	325,0	

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	328,0	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	37,2	
3,00 mm	h 7	114,0	
4,00 mm	h 7	619,6	(200,0)
5,00 mm	h 7	582,3	(267,0)
6,00 mm	h 8	129,1	(2185,2)
8,00 mm	h 8	694,1	(500,0)
10,00 mm	h 8	987,9	(385,0)
12,00 mm	h 8	1784,2	
14,00 mm	h 8	181,4	(300,0)
15,00 mm	h 8	279,7	
16,00 mm	h 9	296,5	(1000,0)
18,00 mm	h 9	481,7	
20,00 mm	h 9	2266,4	(1000,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
22,00 mm	h 9	203,7	(400,0)
25,00 mm	h 9	1872,7	(1300,0)
25,00 mm	h 9	0,0	(1000,0)
30,00 mm	h 9	204,0	(300,0)
35,00 mm	h 9	349,4	(700,0)
36,00 mm	h 9	269,1	(300,0)
40,00 mm	-0/+0.100	3118,2	(1085,5)
40,00 mm	-0/+0.100	3117,9	(1085,5)
		0,0	(235,0)
45,00 mm	-0/+0.100	671,9	
50,00 mm	-0/+0.100	779,7	(500,0)
55,00 mm	-0/+0.100	429,6	
60,00 mm	-0/+0.120	189,3	(1000,0)
65,00 mm	-0/+0.120	676,0	(400,0)
70,00 mm	-0/+0.140	145,8	(600,0)
75,00 mm	-0/+0.140	225,8	(462,0)
80,00 mm	-0/+0.140	959,8	
90,00 mm	-0/+0.200	418,4	
100,00 mm	-0/+0.500	604,6	
110,00 mm	-0/+0.500	299,8	(130,0)
120,00 mm	-0/+0.500	483,6	
130,00 mm	-0/+0.500	664,8	
140,00 mm	-0/+0.500	486,8	
150,00 mm	-0/+0.500	172,0	
160,00 mm	-0/+0.500	50,0	(270,0)
170,00 mm	-0/+0.500	89,4	(310,0)
180,00 mm	-0/+0.500	87,0	(345,0)
190,00 mm	-0/+0.500	195,6	
200,00 mm	-0/+0.500	257,5	
225,00 mm	-0/+0.500	11,0	
230,00 mm	-0/+0.500	100,1	(375,0)
250,00 mm	-0/+0.500	40,0	(555,0)
280,00 mm	-0/+0.500	219,4	
305,00 mm	-0/+0.500	230,5	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
330,00 mm		0,0	(386,0)
350,00 mm	-0/+0.500	74,1	(217,2)

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE

MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Condition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
0,6 x 1000 x 2500	800,0	
0,8x 1000 x 2500	1188,1	
1,0 x 1250 x 3000	1975,8	
1,5 x 1250 x 3000	645,8	
2,0 x 1250 x 3000	198,6	
2,0 x 1250 x 3000	3011,2	
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	1024,0	
4,0 x 1000 x 2000	796,3	(3096,0)
5,0 x 1000 x 2000	333,2	
6,0 x 1000 x 2000	282,8	

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	238,4	
1,0x1000x2000	8,2	
1,5x1000x2000	380,6	
2,0x1000x2000	844,5	
3,0x1000x2000	640,3	
4,0x1000x2000	487,6	
5,0x1000x2000	479,8	
6,0x1000x2000	382,4	
8,0x1500x2500	119,4	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	104,4	
1 x 1000 x 2000	165,0	
1 x 1000 x 2000	13,5	
2 x 1000 x 2000	405,1	
3 x 1000 x 2000	396,0	
3 x 1000 x 2400	177,0	
3 x 1250 x 2500	41,6	
4 x 1000 x 2000	379,5	
5 x 1000 x 2000	228,6	

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	98,0	
12,7 x 12,7	400,3	
15,0 x 60,0	493,5	
19,05 x 19,05	59,4	(200,0)
25,4 x 6,35	150,3	
25,4 x 12,7	291,6	
25,4 x 25,4	86,5	(300,0)
35,0 x 35,0	673,0	

Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	40,0	
1,2 mm	45,0	
2,0 mm	45,0	
2,4 mm	50,0	
3,2 mm	50,0	

Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
-----------	----------	----------



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Welding wire AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	10,0	
2,4 mm	10,0	